

temperature sensor for heat stress

BLACK GLOBE

Campbell Scientific (Canada) Corp.
is pleased to present the
Black Globe
temperature sensor for heat stress

Loss of physical and mental efficiency occurs under definable degrees of heat stress. Severe heat stress can lead to fatigue, exhaustion and possibly even disability or death. The Wet Bulb Globe Temperature Index (WBGT) combines the effects of temperature, humidity, radiant heat, and wind into one single index employed to express environmental heat stress.

The **Black Globe Temperature Sensor for Heat Stress** uses a thermistor inside a 6" hollow copper sphere painted black to measure radiant temperature. This measurement, along with the measurement of ambient air and wet bulb temperatures, may be used to calculate the WBGT index, which is sometimes referred to as the Humidex.



| | |
|--------------------------------------|--|
| Temperature Measurement Range: | -5° to +95°C |
| Temperature Survival Range: | -50° to +100°C |
| Thermistor Interchangeability Error: | Typically $<\pm 0.2^{\circ}\text{C}$ over 0°C to 70°C and ± 0.3 @ 95°C |
| Polynomial Linearization Error: | $\pm 0.5^{\circ}\text{C}$ over -7°C to +90°C |

Heat stress can be reduced by decreasing the lengths of exposure and decreasing the workload of individuals under heat stress. Situation factors such as the type of clothing worn, the type of work performed, the psychological effects of stress, and availability of fluids can also affect the assessment of heat stress. These factors are not easily quantified, and so the individual in a given situation must estimate their significance. Environmental factors such as temperature, humidity, and wind are more easily measured to assess heat stress.

S
C
E
R
S



CAMPBELL SCIENTIFIC
CANADA CORP.

11564 - 149 street - edmonton - alberta - T5M 1W7
tel 780.454.2505 fax 780.454.2655
www.campbellsci.ca

April 2010