

**SC32B OPTICALLY ISOLATED
RS-232 INTERFACE
INSTRUCTION MANUAL**

REVISION: 01/02/03

COPYRIGHT (c) 1987-2003 CAMPBELL SCIENTIFIC, INC.

WARRANTY AND ASSISTANCE

The **SC32B OPTICALLY ISOLATED RS-232 INTERFACE** is warranted by CAMPBELL SCIENTIFIC (CANADA) CORP. ("CSC") to be free from defects in materials and workmanship under normal use and service for **twelve (12) months** from date of shipment unless specified otherwise. CSC's obligation under this warranty is limited to repairing or replacing (at CSC's option) defective products. The customer shall assume all costs of removing, reinstalling, and shipping defective products to CSC. CSC will return such products by surface carrier prepaid. This warranty shall not apply to any CSC products which have been subjected to modification, misuse, neglect, accidents of nature, or shipping damage. This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability or fitness for a particular purpose. CSC is not liable for special, indirect, incidental, or consequential damages.

Products may not be returned without prior authorization. To obtain a Return Merchandise Authorization (RMA), contact CAMPBELL SCIENTIFIC (CANADA) CORP., at (780) 454-2505. An RMA number will be issued in order to facilitate Repair Personnel in identifying an instrument upon arrival. Please write this number clearly on the outside of the shipping container. Include description of symptoms and all pertinent details.

CAMPBELL SCIENTIFIC (CANADA) CORP. does not accept collect calls.

Non-warranty products returned for repair should be accompanied by a purchase order to cover repair costs.



CAMPBELL SCIENTIFIC
C A N A D A C O R P .

11564 - 149 street - edmonton - alberta - T5M 1W7
tel 780.454.2505 fax 780.454.2655

www.campbellsci.ca

SC32B Optically Isolated RS-232 Interface



1. Function

The SC32B interfaces an RS-232 peripheral, commonly a computer or terminal, to the CS I/O of a CSI datalogger. The SC32B has the same functions as the SC32A. Functions include:

1. Converting datalogger logic levels to RS-232 logic levels.
2. Optically isolating the datalogger and the RS-232 peripheral. Optical isolation separates the SC32B into a datalogger section and an RS-232 section. Signals entering from either side are electrically independent, protecting against ground loops, normal static discharge, and noise.
3. Passing data when modem enable pin 5 is high and SDE/printer enable pin 6 is low (normal telecommunications mode).

The SC32B blocks data sent out the datalogger CS I/O port when the SDE/print enable pin 6 is high. This prevents data sent to an SDE device (e.g., storage module) or printer output from being sent out the RS-232 port. The SC32B cannot be configured to pass Instruction 96 serial printer or computer data. Contact Campbell Scientific if this capability is required.

2. Specifications

Operating temperature: -25 to +50°C (typical)

Power: Powered by datalogger, see "Operation" section

Ports: 9 pin female RS-232 configured as DCE. 9 pin male CS I/O

Size: 1.6" x 0.9" x 3" (4.1 x 2.3 x 7.6 cm)

Weight: 1.6 oz. (45.4 g)

3. Connector Descriptions

TABLE 3-1. SC32B Connector Descriptions					
RS-232 9 Pin Female Connector			CS I/O 9 Pin Male Connector		
Pin #	I/O	Description	Pin #	I/O	Description
1	Out	DCD	1	In	+5 V
2	Out	RXD	2		Ground
3	In	TXD	3	Out	Ring
4	In	DTR	4	Out	RX
5		Ground	5	In	ME
6	Out	DSR	6	In	PE (SDE)
7	In	RTS	7		No Connection
8	Out	CTS	8		No Connection
9		No Connection	9	In	TX

3.1 RS-232

The DB9 RS-232 port is configured as Data Communications Equipment (DCE) for direct cable connection to Data Terminal Equipment (DTE). Most computers are configured as DTE. For connection to DCE devices such as modems, the SC932 or SC932A should be used in place of the SC32B.

3.2 9 Pin

The CS I/O port connects to the datalogger through the SC12 Two Peripheral Cable supplied with the SC32B. Pin descriptions and direction (Input/Output) are given in Table 3-1.

4. Operation

Power for the SC32B datalogger section comes from the 5 V supply on pin 1 of the datalogger CS I/O. Communication logic levels to and from the datalogger are referenced to this voltage, ranging from 0 to slightly less than 5 V.

Power for the RS-232 section is isolated from the datalogger 5 V supply via a transformer/isolator. An on-board DC to DC converter supplies the negative voltage required for RS-232 signals.

When the SC32B first receives a character from the RS-232 peripheral (pin 3), 5 V is applied to the datalogger Ring line (pin 3) until the datalogger Modem Enable (ME) goes high, putting the datalogger into the Telecommunications Mode.

5. Application

The SC32B provides a direct interface between the CS I/O port on a Campbell Scientific datalogger and the RS-232 port on a computer. Some Campbell Scientific dataloggers (e.g., the CR23X and CR5000) have a built-in RS-232 port in addition to the CS I/O port. With these dataloggers the SC32B is only necessary if you wish to connect to the CS I/O port instead of the RS-232 port.

The SC32B blocks data sent out the CS I/O port when the datalogger sets the printer enable/SDE (pin 6) high. The SC932 or SC932A (CS I/O to RS-232 DTE interface) can be used to interface to an RS-232 modem.

